

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

SECTION 1: Product and company identification

Product name : Q-208 – Foaming Coil Cleaner CTR
Use of the substance/mixture : Aerosol Cleaner
Product code : 596688 SDS Number: 80219903
Company : Qual-Chem Corp.
PMB #622, 2220 Otay Lakes Rd Ste 502
Chula Vista, CA 91915-1009 - USA
T (866) 962-6168
Emergency number : EMERGENCY # CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Eye Irrit. 2A H319
Skin Sens. 1 H317
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : Extremely flammable aerosol
May cause an allergic skin reaction
Causes serious eye irritation
Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, Do not smoke, open flames, sparks. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Avoid breathing dust, fume, gas, mist, spray, vapors
Wash thoroughly after handling
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves, protective clothing, eye protection, face protection
If on skin: Wash with plenty of water
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Specific treatment (see First aid measures on this label)
If skin irritation or rash occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable
Full text of H-phrases: see section 16

3.2. Mixture

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Glycol Ether EB	(CAS No) 111-76-2	1 - 2.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220 Compressed gas, H280
Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
tetrasodium ethylenediaminetetracetate	(CAS No) 64-02-8	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
(+)-limonene	(CAS No) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. For minor skin contact, avoid spreading material on unaffected skin.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes serious eye irritation. May cause an allergic skin reaction. Extremely flammable.
- Symptoms/injuries after inhalation : Irritation of the nasal mucous membranes.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Under fire conditions closed containers may rupture or explode.
- Explosion hazard : Contents under pressure. Pressurized container: may burst if heated.
- Reactivity : Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stay upwind/keep distance from source. Evacuate unnecessary personnel. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment. Advice local authorities if considered necessary. DO NOT touch spilled material. Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.).

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

Emergency procedures : Do not breathe gas. Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Advise local authorities if considered necessary. Stop leak if safe to do so. Do not contaminate water with the product or its container. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate every possible source of ignition. Prevent the product from entering drains or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Form with air vapors (heavier than air) who stay on the floor. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Isolate area until gas has dispersed. Collect spillage.

Methods for cleaning up : Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Dispose as hazardous waste.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not use if spray button is missing or defective. Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and flame.

Precautions for safe handling : Avoid prolonged and repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Do not breathe gas/vapor/aerosol. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Ground/bond container and receiving equipment. Do not re-use empty containers. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Observe normal hygiene standards. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Do not discharge the waste into the drain.

Hygiene measures : Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Refrigerate.

Storage temperature : < 49 °C

Storage area : Aerosol 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

Personal protective equipment

: Gloves. Protective goggles. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol. Clear, colorless liquid.
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F Estimated
Flash point	: -156 °F Propellant estimated
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.969 g/ml
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Exposure to air.

10.5. Incompatible materials

oxygen. Do not mix with other chemicals. None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

(+)-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight

tetrasodium ethylenediaminetetracetate (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat)
ATE CLP (oral)	500.000 mg/kg body weight

Diethylene Glycol Monoethyl Ether (111-90-0)	
LD50 oral rat	1920 mg/kg

Skin corrosion/irritation : Not classified.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Glycol Ether EB (111-76-2)	
IARC group	3 - Not Classifiable

(+)-limonene (5989-27-5)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified.

Glycol Ether EB (111-76-2)	
LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver
NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day

Aspiration hazard : Not classified
Symptoms/injuries after inhalation : Irritation of the nasal mucous membranes.
Symptoms/injuries after skin contact : May cause an allergic skin reaction.
Symptoms/injuries after eye contact : Causes serious eye irritation.
Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Likely routes of exposure : Skin and eyes contact.;Inhalation

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

(+)-limonene (5989-27-5)	
LC50 fish 1	720 µg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	702 µg/l (96 h; Pimephales promelas)
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)

tetrasodium ethylenediaminetetracetate (64-02-8)	
LC50 fish 1	121 mg/l (96 h; Lepomis macrochirus; Soft water)
EC50 Daphnia 1	625 mg/l (24 h; Daphnia magna)
LC50 fish 2	374 - 792 mg/l (96 h; Lepomis macrochirus; pH > 7)
Threshold limit algae 1	> 100 mg/l (72 h; Scenedesmus subspicatus; Growth)

12.2. Persistence and degradability

(+)-limonene (5989-27-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.
ThOD	3.29 g O ₂ /g substance

tetrasodium ethylenediaminetetracetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 - 0.58 g O ₂ /g substance

12.3. Bioaccumulative potential

(+)-limonene (5989-27-5)	
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).

tetrasodium ethylenediaminetetracetate (64-02-8)	
Log Pow	-2.6
Bioaccumulative potential	Bioaccumulation: not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Contents under pressure. Do not puncture, incinerate or crush.
Waste disposal recommendations	: Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT	: Not regulated for transport
Transport document description	: UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Special Provisions (49 CFR 172.102)	: N82
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306

Q-208 – Foaming Coil Cleaner CTR

Safety Data Sheet

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : AEROSOLS
Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No.(IATA) : UN1950
Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Glycol Ether EB (111-76-2)

(+)-limonene (5989-27-5)

propane (74-98-6)

Not listed on SARA Section 313 (Specific toxic chemical listings)

butane (106-97-8)

Not listed on SARA Section 313 (Specific toxic chemical listings)

tetrasodium ethylenediaminetetracetate (64-02-8)

Diethylene Glycol Monoethyl Ether (111-90-0)

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Oral)

Acute toxicity (oral) Category 4

Q-208 – Foaming Coil Cleaner CTR


Safety Data Sheet

Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H226	Flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.