

# Vanish Carpet Eliminator

## Safety Data Sheet

### SECTION 1: Product and company identification

Product name : Vanish Carpet Eliminator  
Use of the substance/mixture : Cleaner  
Product code : 576279 SDS Number: 84109903  
Company : Qual-Chem Corp.  
PMB #622, 2220 Otay Lakes Rd Ste 502  
Chula Vista, CA 91915-1009 - USA  
T (866) 962-6168  
Emergency number : EMERGENCY # CHEMTREC: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Aerosol 1 H222  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol  
Causes skin irritation  
Causes serious eye irritation

Precautionary statements (GHS-US) :

Keep away from heat, Do not smoke, open flames, sparks. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
Wash thoroughly after handling  
Wear eye protection, face protection, protective gloves  
If on skin: Wash with plenty of water  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Specific treatment (see first aid on this label)  
If skin irritation occurs: Get medical advice/attention  
If eye irritation persists: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve	(CAS No) 111-76-2	2.5 - 10	Not classified

# Vanish Carpet Eliminator

## Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	(CAS No) 112-34-5	2.5 - 10	Eye Irrit. 2A, H319
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220 Compressed gas, H280

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation : Remove the victim into fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash with water and soap. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water fog. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : May liberate toxic gases. Extremely flammable aerosol.

Explosion hazard : Contents under pressure. Contains gas under pressure; may explode if heated.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool tanks/drums with water spray/remove them into safety.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. No flames, No sparks. Eliminate all sources of ignition.

#### 6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : DO NOT touch spilled material. Ventilate spillage area. Advice local authorities if considered necessary.

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Avoid discharge to the environment. Do not allow to enter drains or water courses.

### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate every possible source of ignition. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Clean up any spills as soon as possible, using an absorbent material to collect it.

Methods for cleaning up : Clean thoroughly.

### 6.4. Reference to other sections

No additional information available

# Vanish Carpet Eliminator

## Safety Data Sheet

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Keep away from heat, sparks and flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective.
Precautions for safe handling	: Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof equipment. Do not spray on a naked flame or any incandescent material. Use only outdoors or in a well-ventilated area. Ensure good ventilation of the work station. Avoid breathing dust, fume, gas, mist, spray, vapors. Avoid contact with skin, eyes and clothing. Do not re-use empty containers. Use personal protective equipment as required.
Hygiene measures	: Use good personal hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Pressurized container. Do not puncture, incinerate or crush.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place.
Storage area	: Aerosol 1.
Special rules on packaging	: meet the legal requirements.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr

##### butane (106-97-8)

ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

##### 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)

ACGIH	ACGIH TWA (ppm)	10 ppm
-------	-----------------	--------

##### propane (74-98-6)

ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

#### 8.2. Exposure controls

Appropriate engineering controls	: Provide sufficient air exchange and/or exhaust. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection.
Thermal hazard protection	: Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Consumer exposure controls	: When using do not smoke. Use good personal hygiene practices. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Take off contaminated clothing and wash before reuse.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid. Aerosol.
Odor	: Butyl
Odor threshold	: No data available
pH	: 11 - 12.5 Estimated
Melting point	: No data available
Freezing point	: No data available

# Vanish Carpet Eliminator

## Safety Data Sheet

Boiling point	: 222.87 °F Estimated
Flash point	: -156 °F Propellant estimated
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.99 - 1 g/ml Estimated
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: 230 °C Estimated
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization does not occur.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)

ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
pH: 11 - 12.5 Estimated

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 11 - 12.5 Estimated

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

# Vanish Carpet Eliminator

## Safety Data Sheet

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : This material and its container must be disposed of in a safe manner. Handle unclean empty containers as full ones.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols  
flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

#### ADR

No additional information available

#### Transport by sea

UN-No. (IMDG) : UN1950

Proper Shipping Name (IMDG) : Aerosols

# Vanish Carpet Eliminator

## Safety Data Sheet

Class (IMDG) : 2.1 - Flammable gases

### Air transport

UN-No.(IATA) : UN1950  
Proper Shipping Name (IATA) : Aerosols, Flammable  
Class (IATA) : 2.1 - Gases : Flammable

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### butane (106-97-8)

Not listed on SARA Section 313 (Specific toxic chemical listings)

### propane (74-98-6)

Not listed on SARA Section 313 (Specific toxic chemical listings)

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*